SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Tangit M 3000 Part A
UFI: E69U-2VQ1-Q20H-3V67

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:
Foam, 2-component without propellant gas

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA
Henkelstr. 67
40589 Düsseldorf

Germany

Phone: +49 211 797 0

SDSinfo.Adhesive@henkel.com
For Safety Data Sheet updates please visit our website www.mysds.henkel.com or www.henkel-adhesives.com.

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

Further information is available at Poison Control Centers.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation	Category 2
H315 Causes skin irritation.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Acute toxicity	Category 4
H332 Harmful if inhaled.	
Route of Exposure: Inhalation	
Respiratory sensitizer	Category 1
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
Specific target organ toxicity - single exposure	Category 3
H335 May cause respiratory irritation.	
Target organ: respiratory tract irritation	
Carcinogenicity	Category 2
H351 Suspected of causing cancer.	
Specific target organ toxicity - repeated exposure	Category 2
H373 May cause damage to organs through prolonged or repeated exposure.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:

Contains Diphenylmethane diisocyanate, isomers and homologues

Signal word: Danger

Hazard statement:

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.

Supplemental information	As from 24 August 2023 adequate training is required before industrial or professional use. Further information: https://www.feica.eu/PUinfo
Precautionary statement:	P102 Keep out of reach of children. P101 If medical advice is needed, have product container or label at hand.
Precautionary statement: Prevention	P260 Do not breathe vapors. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/eye protection.
Precautionary statement: Disposal	P501 Dispose of contents/container in accordance with national regulation.

2.3. Other hazards

Information according to XVII. 56 REACH
Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

Following substances are present in a concentration ≥ the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration ≥ the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS No. EC No REACH-Reg. No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	40- < 60 %	Carc. 2, H351 Acute Tox. 4, Inhalation, H332 STOT RE 2, H373 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Resp. Sens. 1, H334 Skin Sens. 1, H317	Eye Irrit. 2; H319; C >= 5 % Skin Irrit. 2; H315; C >= 5 % Resp. Sens. 1; H334; C >= 0,1 % STOT SE 3; H335; C >= 5 % ===== inhalation:ATE = 1,5 mg/l;dust/mist	
4,4'- methylenediphenyl diisocyanate 101-68-8 202-966-0 01-2119457014-47	40- < 60 %	Carc. 2, H351 Acute Tox. 4, Inhalation, H332 STOT RE 2, H373 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Resp. Sens. 1, H334 Skin Sens. 1, H317	Eye Irrit. 2; H319; C >= 5 % Skin Irrit. 2; H315; C >= 5 % Resp. Sens. 1; H334; C >= 0,1 % STOT SE 3; H335; C >= 5 % ===== inhalation:ATE = 1,5 mg/l;dust/mist	
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1 227-534-9 01-2119480143-45	1- < 5 %	STOT RE 2, H373 Carc. 2, H351 Acute Tox. 4, Inhalation, H332 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Skin Sens. 1, H317 Resp. Sens. 1, H334	Eye Irrit. 2; H319; C >= 5 % Skin Irrit. 2; H315; C >= 5 % Resp. Sens. 1; H334; C >= 0,1 % STOT SE 3; H335; C >= 5 % ===== inhalation:ATE = 1,5 mg/l;dust/mist	
2,2'-Methylenediphenyl diisocyanate 2536-05-2 219-799-4 01-2119927323-43	0,1- < 1 %	STOT RE 2, H373 Carc. 2, H351 Acute Tox. 4, Inhalation, H332 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Resp. Sens. 1, H334 Skin Sens. 1, H317	Eye Irrit. 2; H319; C >= 5 % Skin Irrit. 2; H315; C >= 5 % Resp. Sens. 1; H334; C >= 0,1 % STOT SE 3; H335; C >= 5 % ===== inhalation:ATE = 1,5 mg/l;dust/mist	

If no ATE values are displayed, please refer to LD/LC50 values in Section 11.
For full text of the H - statements and other abbreviations see section 16 "Other information".

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:
In case of adverse health effects seek medical advice.

Inhalation:
Move to fresh air, consult doctor if complaint persists.

Skin contact:
Rinse with running water and soap. Skin care. Remove contaminated clothes immediately.

Eye contact:
Immediately flush eyes with soft jet of water or eye rinse solution for at least 5 minutes. If pains remain (intensive smarting, sensitivity to light, visual disturbance) continue flushing and contact/seek doctor or hospital.

Ingestion:
Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed
May cause an allergic skin reaction.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

SKIN: Redness, inflammation.

Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed
See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media
Suitable extinguishing media:
carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:
High pressure waterjet

5.2. Special hazards arising from the substance or mixture
In the event of fire, isocyanate vapors may be formed.
In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

5.3. Advice for firefighters
Wear self-contained breathing apparatus.
Wear protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Wear protective equipment.
Ensure adequate ventilation.
Danger of slipping on spilled product.
Avoid contact with skin and eyes.

6.2. Environmental precautions
Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up
Remove with liquid-absorbing material (sand, peat, sawdust).
Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections
See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Ensure that workrooms are adequately ventilated.
Avoid skin and eye contact.

Hygiene measures:
Do not eat, drink or smoke while working.
Wash hands before work breaks and after finishing work.
Remove any dirt that gets onto the skin with vegetable oil; skin care.

7.2. Conditions for safe storage, including any incompatibilities
Store in sealed original container.
Frost-sensitive
Store in a cool, dry place.
Avoid strictly temperatures below + 2°C and above + 30 °C.
Do not store together with oxidants.
Do not store together with food or other consumables (coffee, tea, tobacco, etc.).
Do not store together with flammable solutions.

7.3. Specific end use(s)
Foam, 2-component without propellant gas

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Germany

Ingredient [Regulated substance]	ppm	mg/m³	Value type	Short term exposure limit category / Remarks	Regulatory list
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9			STEL (Short Term Exposure Limit) factor:	1 Substance listed with both Peak factor and STEL factor. The Peak factor is supplied with the AGW values.	TRGS 900
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9			Skin designation:	Can be absorbed through the skin.	TRGS 900
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9		0,05	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9 [Diisocyanates]			Hazard Designation:		EU_OEL
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9 [Diisocyanates]			Hazard Designation:		EU_OEL
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9 [Diisocyanates]			Short Term Exposure Limit (STEL):	Effective date: 9 April 2026	EU_OEL
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9 [Diisocyanates]			Hazard Designation:		EU_OEL
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9 [Diisocyanates]			Time Weighted Average (TWA):	Effective date: 9 April 2026	EU_OEL
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9 [Diisocyanates]			Time Weighted Average (TWA):	Effective date: 1 January 2029	EU_OEL
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9 [Diisocyanates]			Short Term Exposure Limit (STEL):	Effective date: 1 January 2029	EU_OEL
4,4'-Methylenediphenyl diisocyanate 101-68-8			Skin designation:	Can be absorbed through the skin.	TRGS 900
4,4'-Methylenediphenyl diisocyanate 101-68-8			STEL (Short Term Exposure Limit) factor:	1 Substance listed with both Peak factor and STEL factor. The Peak factor is supplied with the AGW values.	TRGS 900
4,4'-Methylenediphenyl diisocyanate 101-68-8		0,05	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900

4,4'-Methylenediphenyl diisocyanate 101-68-8			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900
4,4'-Methylenediphenyl diisocyanate 101-68-8 [Diisocyanates]			Hazard Designation:		EU_OEL
4,4'-Methylenediphenyl diisocyanate 101-68-8 [Diisocyanates]			Hazard Designation:		EU_OEL
4,4'-Methylenediphenyl diisocyanate 101-68-8 [Diisocyanates]			Time Weighted Average (TWA):	Effective date: 1 January 2029	EU_OEL
4,4'-Methylenediphenyl diisocyanate 101-68-8 [Diisocyanates]			Time Weighted Average (TWA):	Effective date: 9 April 2026	EU_OEL
4,4'-Methylenediphenyl diisocyanate 101-68-8 [Diisocyanates]			Hazard Designation:		EU_OEL
4,4'-Methylenediphenyl diisocyanate 101-68-8 [Diisocyanates]			Short Term Exposure Limit (STEL):	Effective date: 1 January 2029	EU_OEL
4,4'-Methylenediphenyl diisocyanate 101-68-8 [Diisocyanates]			Short Term Exposure Limit (STEL):	Effective date: 9 April 2026	EU_OEL
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1			STEL (Short Term Exposure Limit) factor:	1 Substance listed with both Peak factor and STEL factor. The Peak factor is supplied with the AGW values.	TRGS 900
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1		0,05	Exposure limit(s):	2	TRGS 900
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1 [Diisocyanates]			Time Weighted Average (TWA):	Effective date: 9 April 2026	EU_OEL
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1 [Diisocyanates]			Short Term Exposure Limit (STEL):	Effective date: 1 January 2029	EU_OEL
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1 [Diisocyanates]			Hazard Designation:		EU_OEL
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1 [Diisocyanates]			Short Term Exposure Limit (STEL):	Effective date: 9 April 2026	EU_OEL
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1 [Diisocyanates]			Time Weighted Average (TWA):	Effective date: 1 January 2029	EU_OEL
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1 [Diisocyanates]			Hazard Designation:		EU_OEL
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1 [Diisocyanates]			Hazard Designation:		EU_OEL
2,2'-Methylenediphenyl diisocyanate 2536-05-2			STEL (Short Term Exposure Limit) factor:	1 Substance listed with both Peak factor and STEL factor. The Peak factor is supplied with the AGW values.	TRGS 900
2,2'-Methylenediphenyl diisocyanate 2536-05-2			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900
2,2'-Methylenediphenyl diisocyanate 2536-05-2		0,05	Exposure limit(s):	2	TRGS 900
2,2'-Methylenediphenyl diisocyanate 2536-05-2			Short Term Exposure Limit (STEL):	Effective date: 9 April 2026	EU_OEL

[Diisocyanates]					
2,2'-Methylenediphenyl diisocyanate 2536-05-2 [Diisocyanates]			Hazard Designation:		EU_OEL
2,2'-Methylenediphenyl diisocyanate 2536-05-2 [Diisocyanates]			Hazard Designation:		EU_OEL
2,2'-Methylenediphenyl diisocyanate 2536-05-2 [Diisocyanates]			Short Term Exposure Limit (STEL):	Effective date: 1 January 2029	EU_OEL
2,2'-Methylenediphenyl diisocyanate 2536-05-2 [Diisocyanates]			Hazard Designation:		EU_OEL
2,2'-Methylenediphenyl diisocyanate 2536-05-2 [Diisocyanates]			Time Weighted Average (TWA):	Effective date: 9 April 2026	EU_OEL
2,2'-Methylenediphenyl diisocyanate 2536-05-2 [Diisocyanates]			Time Weighted Average (TWA):	Effective date: 1 January 2029	EU_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
4,4'- methylenediphenyl diisocyanate 101-68-8	aqua (freshwater)		0,0037 mg/l				
4,4'- methylenediphenyl diisocyanate 101-68-8	aqua (intermittent releases)		0,037 mg/l				
4,4'- methylenediphenyl diisocyanate 101-68-8	aqua (marine water)		0,00037 mg/l				
4,4'- methylenediphenyl diisocyanate 101-68-8	sediment (freshwater)				11,7 mg/kg		
4,4'- methylenediphenyl diisocyanate 101-68-8	sediment (freshwater)				1,17 mg/kg		
4,4'- methylenediphenyl diisocyanate 101-68-8	Soil				2,33 mg/kg		
4,4'- methylenediphenyl diisocyanate 101-68-8	Predator						no potential for bioaccumulation
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	aqua (freshwater)		0,0037 mg/l				
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	Freshwater - intermittent		0,037 mg/l				
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	aqua (marine water)		0,00037 mg/l				
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	sediment (freshwater)				11,7 mg/kg		
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	sediment (marine water)				1,17 mg/kg		
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	Soil				2,33 mg/kg		
2,2'-Methylenediphenyl diisocyanate 2536-05-2	aqua (freshwater)		0,0037 mg/l				
2,2'-Methylenediphenyl diisocyanate 2536-05-2	aqua (marine water)		0,00037 mg/l				
2,2'-Methylenediphenyl diisocyanate 2536-05-2	Freshwater - intermittent		0,037 mg/l				
2,2'-Methylenediphenyl diisocyanate 2536-05-2	sediment (freshwater)				11,7 mg/kg		
2,2'-Methylenediphenyl diisocyanate 2536-05-2	sediment (marine water)				1,17 mg/kg		
2,2'-Methylenediphenyl diisocyanate 2536-05-2	Soil				2,33 mg/kg		
2,2'-Methylenediphenyl diisocyanate 2536-05-2	Predator						no potential for bioaccumulation

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
4,4'- methylenediphenyl diisocyanate 101-68-8	Workers	inhalation	Long term exposure - local effects		0,05 mg/m3	no potential for bioaccumulation
4,4'- methylenediphenyl diisocyanate 101-68-8	Workers	inhalation	Acute/short term exposure - local effects		0,1 mg/m3	no potential for bioaccumulation
4,4'- methylenediphenyl diisocyanate 101-68-8	General population	inhalation	Long term exposure - local effects		0,025 mg/m3	no potential for bioaccumulation
4,4'- methylenediphenyl diisocyanate 101-68-8	General population	inhalation	Acute/short term exposure - local effects		0,05 mg/m3	no potential for bioaccumulation
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	Workers	inhalation	Acute/short term exposure - local effects		0,1 mg/m3	
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	Workers	inhalation	Long term exposure - local effects		0,05 mg/m3	
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	General population	inhalation	Acute/short term exposure - local effects		0,05 mg/m3	
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	General population	inhalation	Long term exposure - local effects		0,025 mg/m3	
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	Workers	dermal	Long term exposure - local effects			
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	Workers	dermal	Acute/short term exposure - local effects			
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	General population	dermal	Long term exposure - local effects			
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	General population	dermal	Acute/short term exposure - local effects			
2,2'-Methylenediphenyl diisocyanate 2536-05-2	Workers	inhalation	Acute/short term exposure - local effects		0,1 mg/m3	no potential for bioaccumulation
2,2'-Methylenediphenyl diisocyanate 2536-05-2	Workers	inhalation	Long term exposure - local effects		0,05 mg/m3	no potential for bioaccumulation
2,2'-Methylenediphenyl diisocyanate 2536-05-2	General population	inhalation	Acute/short term exposure - local effects		0,05 mg/m3	no potential for bioaccumulation
2,2'-Methylenediphenyl diisocyanate 2536-05-2	General population	inhalation	Long term exposure - local effects		0,025 mg/m3	no potential for bioaccumulation
2,2'-Methylenediphenyl diisocyanate 2536-05-2	Workers	dermal	Long term exposure - local effects			no potential for bioaccumulation
2,2'-Methylenediphenyl diisocyanate 2536-05-2	Workers	dermal	Acute/short term exposure - local effects			no potential for bioaccumulation
2,2'-Methylenediphenyl diisocyanate 2536-05-2	General population	dermal	Long term exposure - local effects			no potential for bioaccumulation
2,2'-Methylenediphenyl diisocyanate 2536-05-2	General population	dermal	Acute/short term exposure - local effects			no potential for bioaccumulation

Biological Exposure Indices:
None

8.2. Exposure controls:

Respiratory protection:
Suitable breathing mask when there is inadequate ventilation.
Combination filter: ABEKP (EN 14387)
This recommendation should be matched to local conditions.

Hand protection:
Recommended are gloves made from Nitril rubber (Material thickness >0,1 mm, Perforation time < 30s).Gloves should be replaced after each short time contact or contamination. Available at laboratory specialized trade or at pharmacies / chemist's shops.
In the case of longer contact protective gloves made from nitrile rubber are recommended according to EN 374.
material thickness > 0.4 mm
Perforation time > 30 minutes
In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

Eye protection:
Goggles which can be tightly sealed.
Protective eye equipment should conform to EN166.

Skin protection:
Suitable protective clothing
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:
The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.
Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form	liquid
Colour	Light brown
Odor	Neutral
Physical state	liquid
Melting point	Not applicable, Product is a liquid
Solidification temperature	3 °C (37.4 °F)
Initial boiling point (0,6 kPa)	200 °C (392 °F)
Flammability	Not applicable Non flammable product (flash point is greater than 93°C)
Explosive limits	Not applicable, The product is not flammable.
Flash point	230 °C (446 °F)
Auto-ignition temperature	> 250 °C (> 482 °F)
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable, Product reacts with water.
Viscosity (kinematic) (20 °C (68 °F);)	7.000 - 9.000 mm2/s
Viscosity, dynamic (Brookfield; 20 °C (68 °F))	7.000 - 9.000 mPa.s no method / method unknown
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Reacts slowly with water to liberate carbon dioxide gas.
Partition coefficient: n-octanol/water	Not applicable Mixture
Vapour pressure (20 °C (68 °F))	0,001 Pa
Density (20 °C (68 °F))	1,18 - 1,22 g/cm3 no method / method unknown
Relative vapour density:	Currently under determination

Particle characteristics	Not applicable Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity
Reaction with water, alcohols, amines.
Reaction with water, formation of CO2
Pressure build-up in closed containers.

10.2. Chemical stability
Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions
See section reactivity

10.4. Conditions to avoid
Humidity

10.5. Incompatible materials
See section reactivity.

10.6. Hazardous decomposition products
At higher temperatures isocyanate may be released.
Carbon dioxide is generated under contact with moisture, leading to pressure in the cans. Danger of cans bursting!

SECTION 11: Toxicological information

General toxicological information:
Cross-reactions with other isocyanate compounds are possible.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	LD50	> 10.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
4,4'- methylenediphenyl diisocyanate 101-68-8	LD50	> 2.000 mg/kg	rat	other guideline:
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	LD50	> 2.000 mg/kg	rat	other guideline:
2,2'-Methylenediphenyl diisocyanate 2536-05-2	LD50	> 2.000 mg/kg	rat	EU Method B.1 (Acute Toxicity (Oral))

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	LD50	> 9.400 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
4,4'- methylenediphenyl diisocyanate 101-68-8	LD50	> 9.400 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	LD50	> 9.400 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	LD50	> 9.400 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	Acute toxicity estimate (ATE)	1,5 mg/l	dust/mist	4 h		Expert judgement
4,4'- methylenediphenyl diisocyanate 101-68-8	Acute toxicity estimate (ATE)	1,5 mg/l	dust/mist	4 h		Expert judgement
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	Acute toxicity estimate (ATE)	1,5 mg/l	dust/mist	4 h		Expert judgement
2,2'-Methylenediphenyl diisocyanate 2536-05-2	Acute toxicity estimate (ATE)	1,5 mg/l	dust/mist	4 h		Expert judgement

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
4,4'- methylenediphenyl diisocyanate 101-68-8	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	irritating		human	Weight of evidence
4,4'- methylenediphenyl diisocyanate 101-68-8	irritating		human	Weight of evidence

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	sensitising	Skin sensitisation	guinea pig	OECD Guideline 406 (Skin Sensitisation)
4,4'- methylenediphenyl diisocyanate 101-68-8	sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
4,4'- methylenediphenyl diisocyanate 101-68-8	sensitising	Respiratory sensitisation	guinea pig	not specified
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	sensitising	Respiratory sensitisation	guinea pig	not specified
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	sensitising	Respiratory sensitisation	guinea pig	not specified

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EU Method B.13/14 (Mutagenicity)
4,4'- methylenediphenyl diisocyanate 101-68-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EU Method B.13/14 (Mutagenicity)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
4,4'- methylenediphenyl diisocyanate 101-68-8	negative	inhalation		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	negative	inhalation		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	negative	inhalation		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	carcinogenic	inhalation: aerosol	2 y 6 h/d	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
4,4'- methylenediphenyl diisocyanate 101-68-8	carcinogenic	inhalation: aerosol	2 y 6 h/d	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	carcinogenic	inhalation: aerosol	2 y 6 h/d, 5 d/w	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	carcinogenic	inhalation: aerosol	2 y 6 h/d, 5 d/w	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

No data available.

STOT-single exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Assessment	Route of exposure	Target Organs	Remarks
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	May cause respiratory irritation.			
4,4'- methylenediphenyl diisocyanate 101-68-8	May cause respiratory irritation.			

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	NOAEL 0,0002 mg/l	inhalation: aerosol	2 y 6 h per d, 5 d per week	rat	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
4,4'- methylenediphenyl diisocyanate 101-68-8	NOAEL 0,0002 mg/l	inhalation: aerosol	main: 2 y; satellite:1 y 6 h/d; 5 d/w	rat	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	NOAEL 0,2 mg/m³	inhalation: aerosol	2 y 6 h/d, 5 d/w	rat	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	NOAEL 0,2 mg/m³	inhalation: aerosol	2 y 6 h/d, 5 d/w	rat	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	LC50	> 1.000 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	LL50	> 100 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	LC50	Toxicity > Water Solubility	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	LC50	Toxicity > Water solubility	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	EC50	> 1.000 mg/l	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	EC50	> 100 mg/l	48 h	Daphnia magna	EU Method C.2 (Acute Toxicity for Daphnia)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	EC50	Toxicity > Water Solubility	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	EC50	Toxicity > Water solubility	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	NOEC	10 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	NOEC	10 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
o-(p-Isocyanatobenzyl)phenyl	NOEC	Toxicity > Water	21 day	Daphnia magna	OECD 211 (Daphnia

isocyanate 5873-54-1		solubility			magna, Reproduction Test)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	NOEC	Toxicity > Water solubility	21 day	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	EC50	> 1.640 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	EL50	> 100 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	NOELR	100 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	EC50	Toxicity > Water Solubility	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	NOELR	Toxicity > Water Solubility	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	EC50	Toxicity > Water solubility	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	NOELR	Toxicity > Water solubility	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	EC50	> 100 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	EC50	> 1.000 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	not inherently biodegradable	aerobic	0 %	28 d	OECD Guideline 302 C (Inherent Biodegradability: Modified MITI Test (II))
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	not readily biodegradable.	not specified	0 %	28 d	OECD 301 A - F
4,4'- methylenediphenyl diisocyanate 101-68-8	not readily biodegradable.	aerobic	0 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	not inherently biodegradable	aerobic	0 %	28 d	OECD Guideline 302 C (Inherent Biodegradability: Modified MITI Test (II))
2,2'-Methylenediphenyl diisocyanate 2536-05-2	not inherently biodegradable	aerobic	0 %	28 day	OECD Guideline 302 C (Inherent Biodegradability: Modified MITI Test (II))

12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	200			Cyprinus carpio	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	92 - 200	28 d		Cyprinus carpio	OECD Guideline 305 E (Bioaccumulation: Flow-through Fish Test)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	200	28 day		Cyprinus carpio	OECD Guideline 305 E (Bioaccumulation: Flow-through Fish Test)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	200	28 day		Cyprinus carpio	OECD Guideline 305 E (Bioaccumulation: Flow-through Fish Test)

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
4,4'- methylenediphenyl diisocyanate 101-68-8	4,51	22 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	5,22		QSAR (Quantitative Structure Activity Relationship)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	5,22		QSAR (Quantitative Structure Activity Relationship)

12.5. Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or vPvB.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:
Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:
Empty PU foam canisters should be returned in the original carton to PDR GmbH, D-95449 Thurnau (free of charge collection service under tel.: 0800-783 6736, Fax: 0800-783 6737, Germany) for recycling. Individual containers should be disposed of at communal collection points.
Use packages for recycling only when totally empty.

Waste code
08 05 01

SECTION 14: Transport information

14.1. UN number or ID number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 2024/590):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable

National regulations/information (Germany):

WGK: WGK 1: slightly hazardous to water (Ordinance on facilities for handling substances that are hazardous to water (AwSV))
Classification according to AwSV, Annex 1 (5.2)

BG regulations, rules, infos:
BG regulation: BGV B 1 Handling hazardous substances
Storage class according to TRGS 510: 10

15.2. Chemical safety assessment
A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.

Abbreviations and acronyms:

ADG(-Code): Australian Dangerous Goods (Code)
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
ASTM: American Society for Testing and Materials
ATE: acute toxicity estimate
AS: Australian Standard
AwSV: Ordinance on Installations for the Handling of Substances Hazardous to Water
CAS: Chemical Abstract Service
CLP: Regulation (EC) No 1272/2008
CMR: cancerogenic, mutagenic or reprotoxic
DIN: German Institute for Standardization
ECx: Effective concentration (x% effective level)
ECHA: European Chemicals Agency
EC-Nummer: Substance number in the EU-inventories EINECS/ELINCS
ECTLV: European community threshold limit value
ED:Substance identified as having endocrine disrupting properties
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
EN : European Standard
ENCS: Japanese chemical inventory
EPA: US Environmental Protection Agency
EU: European Union
EU EXPLD1: Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD2: Substance listed in Annex II, Reg (EC) No. 2019/1148
EWC: European Waste Catalogue
GHS: Globally Harmonised System for Classification and Labelling of Chemicals
GLP: Good Laboratory Practice
HSNO: Hazardous Substances and New Organisms
IARC: International Agency for Research of Cancer
IATA: International Air Transport Association
IBC-Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50: half maximal inhibitory concentration
ICAO: International Civil Aviation Organization
IMDG-Code: International Maritime Code for Dangerous Goods
IMO: International Maritime Organization
ISO: International Standardization Organisation
LC50: Median lethal concentration
LD50: Median lethal dose
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
n.o.s.: not otherwise specified
NO(A)EC: No (adverse) effect concentration
NO(A)EL: No (adverse) effect level
NZS: New Zealand Standard
OECD: Organisation for Economic Co-operation and Development
OEL: Occupational Exposure Limit
OPPT: US EPA Office of Pollution Prevention and Toxics
OPPTS: US EPA Office of Prevention, Pesticides and Toxic Substances
PBT: Persistent, bioaccumulative, toxic
(Q)SAR: (Quantitative) structure–activity relationship
REACH: Regulation (EC) No. 1907/2006

RID: Regulations concerning the International Transport of Dangerous Goods by Rail
SADT: Self Accelerating Decomposition Temperature
SDS: Safety Data Sheet
STOT: Specific Target Organ Toxicity
STOT SE: Specific Target Organ Toxicity - single exposure
STOT RE: Specific Target Organ Toxicity - repeated exposure
SUSMP: Standard for the Uniform Scheduling of Medicines and Poisons
SVHC: Substance of very high concern (REACH Candidate List)
TRGS: German Technical Rules for hazardous substances
UN: United Nations
VOC: Volatile Organic Compound
814.018 VOC Reg CH: Swiss Ordinance 814.018 on the Incentive Tax on Volatile Organic Compounds
vPvB: Very persistent, very bioaccumulative
VwVwS: Administrative Regulation on Substances Hazardous to Waters
WGK: Water hazard class

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel´s Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.